



DWG NO.
C-101287

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.

LDC
-
DIST
-



TOP-LINK



Notes:

Material:

1)Plunger & Body : CuZn36 Pb3, H02 (C36000)
or CuZn39 PB3 or CuZn38 PB2.

2)Spring : Stainless steel wire

2 Plating

1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating

2)Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating

3 Mechanical

1)Total stroke : 1.2mm

2)Durability: 10,000 cycle min.

4 Electrical

1)Contact resistance: 30mOhm Max.

2)Operating voltage: 36VDC

DIMENSIONS IN MM				MATL		HT TR		FIN	
TOLERANCES UNLESS				1		—		—	
OTHER SPECIFIED				DWN		APVD		Top-Link	
0 = ±				Jim		Lansing		Electronics	
0.0 = ±0.15				CHK		REL		Top-Link	
0.000 = ±				Andy				Electronics Ltd.	
ANGLE: ±1°				NAME		POGO PIN			
SURF TEXTURE: 32/				SCALE		DWG		SHEET	
REMOVE BURRS, BREAK				1:1		NO.		1 OF 1	
SHARP EDGES R0.05 MAX				A4		C-101287		REV	
DO NOT SCALE PRINT								A	

USED ON

-

101287-1

PART NUMBER

A

B

C

D

4

3

2

1