




TOP-LINK

- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M.
 - 2 Mechanical performance(See the table 1)
 - <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
 - <2.2>Warning:Working height are not permitted to be less than Min working height.
 - 3 Electrical performance
 - <3.1>Current rating: 2.0A
 - <3.2>Voltage rating: 36VAC/DC
 - <3.3>Dynamic Resistance: 30mOhm Max. (between max and min working height)
 - 4 Environmental performance
 - <4.1>RoHS compliant.
 - <4.2>Salt Spray:48h Min
 - <4.3>Operating Temperature range: -40°C~+85°C
 - <4.4>Withstanding Higt Temperature: 260°C/10Sec
 - 5 Packaging: Bag

Table 1:Mechanical performance		
Working Height	5.50mm	50±15gf
Durability	10000 Cycles Min.	

Item	Part Name	Q'ty	Material	Finish
3	Body	1	Leaded Brass	Au plating 0.1um min Ni plating 1.4um min
2	Plunger	1	Leaded Brass	Au plating 0.4um min Ni plating 1.4um min
1	Spring	1	Stainless steel wire	-----

Top-Link Electronics Ltd		TOLERANCES UNLESS OTHER SPECIFIED	
DWN:		0.0 = ± 0.15	
CHK:		0.00 = ± 0.10	
NAME		Angle: ±1°	
Scale		SURF. TEXTURE: BREAK SHARP EDGES R0.05 MAX.DO NOT SCALE PRINT.	
1:1	Size A4	Part NO.	20101011508
Pogo PIN		Page	1/1
		Rev:	1

top-link