






proposal



- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M-1994.
 - 2 Mechanical performance(See the table 2)
 - <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
 - <2.2>Warning: Working height are not permitted to be less than Min working height.
 - 3 Electrical performance
 - Resistance: 30mOhm Max.; Current: 2A DC
 - 4 Packaging Spec.
 - 5 RoHS compliant.

TOP-LINK

Item	Part name	Qty/Ea'	Material	Finish
1	HSG	1	High Temp. Plastic UL94 V-0 Color Black	_____
2	Body	5	Leaded Brass	Gold plating over Nickel plating
3	Plunger	5	Leaded Brass	Gold plating over Nickel plating
4	Spring	5	Stainless steel wire	_____
5				

Table 2 Mechanical performance			
The Min.working Stroke	0.80mm	80gf min<2.1>	
The Max.working Stroke	1.10mm	160gf max	
Durability		10000 cycle	

Top-Link Electronics Ltd.		Type	Unit		Weight								
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Customer drawing	mm									
0.0 = ± 0.15		CHK:	Qin Zuozhong	APVD:									
0.00 = ± 0.10		REL:											
Angle: ±11°		Name Customer drawing											
SURF. TEXTURE:													
REMOVE BURRS.													
BREAK SHARP EDGES													
R0.05 MAX.DO NOT SCALE PRINT.		Scale	Size	DWG No.	Page	Rev.							
		1:1	A4	C-100814	1/1	1							

100814-5
PART NUMBER

Top-Link Electronics Ltd.

	NEW	2012/05/09
Rev.	Revision record.	Date.