



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3 Electrical performance
- 4 RoHS compliant.

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating over Ni 1.4um min plating A.1.
2	Plunger	2	Leaded Brass	Au 0.4um plating over Ni 1.4um min plating A.1.
3	Spring	1	Stainless steel wire	_____
4				
5				

Table 1 Mechanical performance			
Max.working height	9.20mm	80gf min<2.1>	
Min.working height	8.50mm	200gf max	
Durability	10000cycle		

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Gui zhiguo	APVD:		<div><div><i>Top-Link</i></div><div><i>Electronics</i></div></div> <div>Top-Link Electronics Ltd.</div>	
0.0 = ± 0.15		CHK:		REL:			
0.00 = ± 0.10							
0.000 = ± 0.005							
Angle: ±1°							
SURF. TEXTURE: REMOVE BURRS.							
BREAK SHARP EDGES							
R0.05 MAX.DO NOT SCALE PRINT.		Scale	Size	DWG No.	Page		Rev.
		1:1	A4	C-101755	1/1		1

DIST  
---

1.1	update	2013/09/22
1	NEW	2012/06/13
Rev.	Revision record.	Date.

4

3

2

1